











Figure 9. Queuing delay of *WoW* traffic (always using TCP SACK) when using different TCP versions for the background FTP source

For the smaller, 20-packet buffer, there is some packet loss, so both TCP SACK and TCP *New Reno* adapt their sending window accordingly. Interestingly, as they also keep on increasing their rate, they affect the *WoW* flow, which reduces its window (Figs. 6 and 7). TCP *Vegas* (Fig. 8), on the other hand, has a similar behavior to that for the larger, 200-packet buffer: it maintains its window size, which results in smaller delays for the game traffic, as shown in Fig. 9.

## V. CONCLUSIONS

The results show that TCP *Vegas* is able to maintain a constant rate while competing with the game traffic, since it prevents packet loss by avoiding the increase of the sending window size. Opposite to that, TCP SACK and TCP *New Reno* tend to keep on increasing the window size, thus adding undesired delays to the game traffic. Finally, smaller buffers have been demonstrated to be better for TCP-based MMORPGs, since larger buffers cause higher delays.

As future work, we plan to run simulations with more recent TCP variants (e.g., TCP *Libra*), both for gaming and for background traffic, in order to check its suitability in these scenarios, also taking into account their coexistence with widely deployed TCP variants.

## ACKNOWLEDGMENT

This work has been partially financed by CPUFLIPI Project (MICINN TIN2010-17298), the European Community's 7th Framework Programme under grant agreement no. 285939 (ACROSS), MBACToIP Project, of Aragon I+D and Ibercaja Obra Social, Project Catedra Telefonica, Univ. Zaragoza.

## REFERENCES

[1] Ubicom White Paper, "OPScore, or Online Playability Score: A Metric for Playability of Online Games with Network Impairments," 2005, <http://www.kevingee.biz/wp-content/uploads/2011/04/IP3K-DWP-OPSCORE-10.pdf>

[2] M. Oliveira, T. Henderson, "What online gamers really think of the Internet?," in Proc. 2nd workshop on Network and system support for games (NetGames '03). ACM, New York, NY, USA, pp. 185-193, 2003.

[3] K.-T. Chen, P. Huang, C.-L. Lei, "How sensitive are online gamers to network quality?," *Comm. of the ACM*, vol. 49, no. 11, pp. 34-38, 2006.

[4] V. Paxson, "Empirically-Derived Analytic Models of Wide-Area TCP Connections," *IEEE/ACM Transactions on Networking*, vol. 2, no. 2, pp. 316-336, 1994.

[5] M.S Borella, "Source Models of Network Game Traffic," *Networkworld + Interop'99 Engineer's Conf.*, 1999.

[6] P. Svoboda, W. Karner, M. Rupp, "Traffic Analysis and Modeling for World of Warcraft," in Proc. ICC, Urbana-Champaign, IL, USA 2007.

[7] Y. Wu, H. Huang, D. Zhang, "Traffic Modeling for Massive Multiplayer On-line Role Playing Game (MMORPG) in GPRS Access Network," in Proc. of the Int. Conf. on Communications, Circuits and Systems, pp. 1811-1815, 2006.

[8] J. Kim, E. Hong, J. Choi, "Measurement and Analysis of a Massively Multiplayer Online Role Playing Game Traffic," in Proc. of Advanced Network Conf., pp. 1-8, 2003.

[9] X. Wang, T.T. Kwon, Y. Choi, M. Chen, Y. Zhang, "Characterizing the Gaming Traffic of World of Warcraft: From Game Scenarios to Network Access Technologies," *IEEE Network* 26(1), pp. 27-34, 2012.

[10] H. Park, T. Kim, S. Kim, "Network traffic analysis and modeling for games," in *Internet and Network Economics*, ser. Lecture Notes in Computer Science. Springer Berlin / Heidelberg, pp. 1056-1065, 2005.

[11] M. Suznjevic, I. Stupar, M. Matijasevic, "Traffic modeling of player action categories in a MMORPG," in Proc. 2nd workshop on Distributed Simulation and Online gaming (DISIO), p. 8, 2011.

[12] M. Ries, P. Svoboda, M. Rupp, "Empirical study of subjective quality for Massive Multiplayer Games," Proc. of the 15th Int. Conf. on Systems, Signals and Image Processing, pp.181-184, 2008.

[13] L. S. Brakmo, S. W. O'Malley, L. L. Peterson, "TCP vegas: New techniques for congestion detection and avoidance," in SIGCOMM'94, London, UK, 1994.

[14] S. H. Low, L. Peterson, L. Wang, "Understanding TCP vegas: a duality model," *SIGMETRICS Perform. Eval. Rev.* Vol. 29, No. 1, June 2001, pp. 226-235.

[15] C. Caini, R. Ferrincelli, "TCP hybla: A TCP enhancement for heterogeneous networks," *Int. Journal of Satellite Communications and Networking*, vol. 22, pp. 547-566, 2004.

[16] G. Marfia, C. E. Palazzi, G. Pau, M. Gerla, M. Roccetti, "TCP Libra: Derivation, analysis, and comparison with other RTT-fair TCPs," *Computer Networks*, Volume 54, Issue 14, 6, pp. 2327-2344, 2010.

[17] A. Vishwanath, V. Sivaraman, G. N. Rouskas, "Considerations for Sizing Buffers in Optical Packet Switched Networks," in IEEE INFOCOM, Brazil, 2009.

[18] C.E. Palazzi, S. Ferretti, M. Roccetti, G. Pau, M. Gerla, "What's in that Magic Box? The Home Entertainment Center's Special Protocol Potion, Revealed," *IEEE Transactions on Consumer Electronics*, vol. 52, no. 4, 1280-1288, 2006.

[19] G. Marfia, M. Roccetti, "TCP At Last: Reconsidering TCP's Role for Wireless Entertainment Centers at Home," *IEEE Transactions on Consumer Electronics*, vol. 56, n. 4, Nov. 2010, pp. 2233-2240

[20] C. Griwodz, P. Halorsen, "The fun of using TCP for a MMORPG," in Proc. of the 2006 Int. workshop on Network and operating systems support for digital audio and video, 2006, pp. 1:1-1:7.

[21] M. Suznjevic, O. Dobrijevic, M. Matijasevic, "MMORPG Player actions: Network performance, session patterns and latency requirements analysis," *Multimedia Tools & Appl.* Vol. 45, no. 1-3, pp. 191-214, 2009.

[22] AT&T Global IP Network, <http://ipnetwork.bgtmo.ip.att.net/pws>

[23] M. Enachescu, Y. Ganjali, A. Goel, N. McKeown, T. Roughgarden, "Part III: routers with very small buffers," *SIGCOMM Comput. Commun. Rev.* Vol 35, no. 3, pp. 83-90, 2005.